## NSN 5985-01-032-7911



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-032-7911 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 2.480 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.750 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.750 inches **Overall Height:** 1.620 inches **Overall Width:** 1.310 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.200 inches **Operating Tempurature Range:** -54.0/+85.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 **Coaxial Connector Series Designation:** Sma **Power Rating:** 3.0 watts average **Mounting Facility Screw Thread Series Designator:** Unc **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.2 **Overall Attenuation Range In Decibels:** +0.0/+20.0 **Attenuation Variation Method:** Stepped **Step Position Quantity: Attenuation Per Step In Decibels:** 2.0

**Mounting Facility Type And Quantity:** 

4 threaded hole

**Frequency Range:** 

Between 0.000 megahertz and 1000.000 megahertz

## NSN 5985-01-032-7911

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Shaft Type:
Round, slotted
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A223a0