

View Online at <https://aerobasegroup.com/nsn/5985-01-033-8793>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

2.480 inches all flanges and 2.520 inches all flanges

Flange Outside Height:

1.730 inches all flanges and 1.770 inches all flanges

Flange Depth:

0.480 inches all flanges and 0.520 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.171 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.01

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Criticality Code Justification:

Feat

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Waveguide Longer Offset Distance:

1.750 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

Waveguide Offset Distance:

1.750 inches

Special Features:

Two attached nipples facing forward toward flange; water colled

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

Precious Material And Location:

Internal waveguide surface silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment inside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0