## NSN 5985-01-035-5242

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-035-5242

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend h-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.313 inches second flange

Flange Outside Height:

1.312 inches first flange

Flange Inside Diameter:

0.710 inches first flange

Flange Depth:

0.375 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange single connection facility

**Voltage Standing Wave Ratio:** 

1.05

**Waveguide Outside Width:** 

0.702 inches

**Thread Size:** 

0.138 inches first flange single connection facility

Waveguide Inside Width:

0.622 inches

**Waveguide Inside Height:** 

0.311 inches

**Waveguide Outside Height:** 

0.391 inches

**Waveguide Longer Offset Distance:** 

2.338 feet

Flange Connecting Facility And Quantity:

2 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

## **NSN 5985-01-035-5242** Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
9.062 inches
Flexibility:
Rigid single tubing segment
Material:
Copper alloy single tubing segment
Surface Treatment:
Any acceptable all tubing segment and flange all surfaces
Style Designator:
Corner type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0