NSN 5985-01-035-6911

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-01-035-6911

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
6.600 inches
Overall Height:
3.130 inches
Overall Width:
1.700 inches
Coaxial Connector Series Designation:
Sma
Overall Attenuation Range In Decibels:
+0.0/+11.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
11
Attenuation Per Step In Decibels:
Attenuation Per Step In Decibels: 1.0
·
1.0
1.0 Mounting Facility Type And Quantity:
1.0 Mounting Facility Type And Quantity: 2 connector
1.0 Mounting Facility Type And Quantity: 2 connector Frequency Range:
1.0 Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz
1.0 Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity:
1.0 Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity:
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female Shelf Life:
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female Shelf Life: N/a
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female Shelf Life: N/a
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female Shelf Life: N/a Unit Of Measure:
Mounting Facility Type And Quantity: 2 connector Frequency Range: Between 0.000 gigahertz and 4.000 gigahertz Adjustment Device Type And Quantity: 1 electronic, programmable Terminal Type And Quantity: 3 connector, coaxial, female Shelf Life: N/a Unit Of Measure: Demilitarization: