NSN 5985-01-035-7464

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-035-7464

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
0.860 inches
Overall Diameter:
0.280 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25 and 1.45 and 1.65
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
Rf Signal Attenuation In Decibels: 6.0
6.0
6.0 Voltage Standing Wave Ratio Frequency Range:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Female output and male input
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Female output and male input Mounting Method:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Female output and male input Mounting Method: Connector
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz and +12.4/+18.0 gigahertz Attenuation Accuracy Reference Frequency: 18.0 gigahertz Attenuation Accuracy In Decibels: -1.00/+1.00 Connection Type Per Function: Female output and male input Mounting Method: Connector Terminal Type And Quantity: 2 connector

Fsc Application Data:

Antennas, waveguides, and related equipment

NSN 5985-01-035-7464

Fixed Attenuator - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000