## NSN 5985-01-036-2214

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-036-2214

Application Design:
Transmission line
Body Material:
Aluminum alloy
Body Style:
Err-090
Body Surface Treatment:
Enamel, mil-e-15090, type 2, class 2
Overall Length:
Between 4.050 inches and 4.110 inches
Overall Diameter:
Between 0.720 inches and 1.030 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.05
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
72.5 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
1.0
Connection Type Per Function:
Male input and female output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 850.000 megahertz and 942.000 megahertz
Special Features:
Ends labelled input and output
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:

N/a **Unit Of Measure:** 

## NSN 5985-01-036-2214

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000