NSN 5985-01-036-6214

Fixed Attenuator - Page 1 of 2

Application Design: Transmission line



View Online at https://aerobasegroup.com/nsn/5985-01-036-6214

Body Material:						
Steel, stainless						
Body Style:						
Err-090						
Body Surface Treatment:						
Any acceptable						
Overall Length:						
2.000 inches						
Overall Diameter:						
0.830 inches						
Operating Tempurature Range:						
-55.0/+125.0 degrees celsius						
Voltage Standing Wave Ratio:						
1.07						
Input Impedance Rating In Ohms:						
50.0						
Output Impedance Rating In Ohms:						
50.0						
Coaxial Connector Series Designation:						
N						
Power Rating:						
2.0 watts average and 500.0 watts peak						
Rf Signal Attenuation In Decibels:						
10.0						
Attenuation Accuracy Reference Frequency:						
12.4 gigahertz						
Attenuation Accuracy In Decibels:						
-0.30/+0.30						
Frequency Sensitivity Attenuation In Decibels:						
0.05						
Connection Type Per Function:						
Female input and male output						
Mounting Method:						
Connector						
Terminal Type And Quantity:						
2 connector						
Frequency Range:						
Between 0.000 hertz and 12.400 gigahertz						
Fsc Application Data:						
Antennas, waveguides, and related equipment						

NSN 5985-01-036-6214

Fixed Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000