NSN 5985-01-036-6215

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-036-6215

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 2.895 inches |
| Overall Height: |
| 2.438 inches |
| Overall Width: |
| 1.875 inches |
| Distance Between Mounting Facility Centers: |
| 1.125 inches |
| Voltage Standing Wave Ratio: |
| 1.20 and 1.50 |
| Coaxial Connector Series Designation: |
| Bnc |
| Power Rating: |
| 1.0 watts peak |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Overall Attenuation Range In Decibels: |
| +0.0/+10.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 10 |
| Attenuation Per Step In Decibels: |
| 1.0 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Frequency Range: |
| Between 0.000 gigahertz and 2.000 gigahertz |
| Mounting Thread Quantity: |
| 32 per inch |
| Adjustment Device Type And Quantity: |
| 1 knob |
| Mounting Facility Pattern: |
| Two position in-line |
| Mounting Facility Screw Thread Diameter: |
| 0.164 inches |
| Impedance Rating In Ohms: |
| |

NSN 5985-01-036-6215

Variable Attenuator - Page 2 of 2



| Terminal Type And Quantity | /: |
|----------------------------|----|
|----------------------------|----|

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0