## NSN 5985-01-037-1725



Fixed Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-037-1725 **Application Design:** Transmission line **Body Material:** Metal **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 2.656 inches **Overall Diameter:** 0.812 inches **Operating Tempurature Range:** -25.0/+150.0 degrees fahrenheit **Voltage Standing Wave Ratio:** 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 2.0 watts average and 200.0 watts peak **Rf Signal Attenuation In Decibels:** 5.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+6.0 gigahertz and +6.0/+12.4 gigahertz **Attenuation Accuracy Reference Frequency:** 12.4 gigahertz **Frequency Sensitivity Attenuation In Decibels: Connection Type Per Function:** Female output and male input **Unpackaged Unit Weight:** 2.400 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

## NSN 5985-01-037-1725

Fixed Attenuator - Page 2 of 2



	Fsc	Ap	olication	Data:
--	-----	----	-----------	-------

Antennas, waveguides, and related equipment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000