## NSN 5985-01-037-8350



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-037-8350 **Application Design:** Transmission line **Body Style:** Coaxial type **Overall Length:** 1.440 inches **Overall Height:** 1.790 inches **Overall Width:** 1.090 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches **Distance Between Mounting Facility Centers:** 1.094 inches **Operating Tempurature Range:** -0.0/+60.0 degrees celsius **Voltage Standing Wave Ratio:** 1.60 **Coaxial Connector Series Designation:** Sma **Power Rating:** 500.0 milliwatts average **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 1.4 **Overall Attenuation Range In Decibels:** +0.0/+10.0 **Attenuation Variation Method:** Continuous **Mounting Facility Type And Quantity:** 2 unthreaded hole Frequency Range: Between 250.000 megahertz and 450.000 megahertz **Overall Attenuation Accuracy In Decibels:** -1.00/+1.00 **Adjustment Device Type And Quantity:** 1 knob **Mounting Facility Pattern:** 

Two position in-line
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female

## NSN 5985-01-037-8350

Variable Attenuator - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0