

View Online at <https://aerobasegroup.com/nsn/5985-01-037-9752>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

1.630 inches

Overall Height:

3.680 inches

Overall Width:

1.630 inches

Scale Linearity:

Linear

Scale Division Quantity:

6

Operating Temperature Range:

-0.0/+54.0 degrees celsius

Voltage Standing Wave Ratio:

1.40

Power Rating:

2.0 watts average and 200.0 watts peak

Mounting Facility Screw Thread Series Designator:

Unef

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0/+60.0

Attenuation Accuracy Reference Frequency:

12.4 gigahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

6

Attenuation Per Step In Decibels:

10.0

Frequency Range:

Between 0.000 gigahertz and 12.400 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.20/+1.20

Segment Attenuation Range In Decibels:

+0.00/+20.00 and +20.00/+30.00 and +30.00/+40.00 and +40.00/+50.00 and +50.00/+60.00

Segment Attenuation Accuracy In Decibels:

-0.50/+0.50 and -0.60/+0.60 and -0.80/+0.80 and -1.00/+1.00 and -1.20/+1.20

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Screw Thread Diameter:

0.375 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A223a0