NSN 5985-01-039-3793

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-039-3793

A collection Boots
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
10.542 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
8.376 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.100 inches
Overall Height:
1.240 inches
Overall Width:
2.050 inches
Scale Linearity:
Linear
Scale Division Quantity:
110
Operating Tempurature Range:
-40.0/+85.0 degrees celsius
Coaxial Connector Series Designation:
Sma
Power Rating:
3.3 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.8
Overall Attenuation Range In Decibels:
+0.0/+110.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
11
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 gigahertz and 18.000 gigahertz
Mounting Thread Quantity:

32 per inch

NSN 5985-01-039-3793

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity: 4 motor Mounting Facility Pattern: Four position rectangular Mounting Facility Screw Thread Diameter: 0.138 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: --Demilitarization:

Yes - demil/mli

Fiig: A223a0