NSN 5985-01-040-3122

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-040-3122

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

Bend Angle In Deg:

90.0 second bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.872 inches all flanges

Flange Inside Height:

0.872 inches all flanges

Flange Outside Diameter:

3.625 inches all flanges

Flange Depth:

0.938 inches all flanges

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.02

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

2.000 inches

Thread Size:

0.190 inches all flanges all connection facilities

Waveguide Inside Width:

1.872 inches

Waveguide Inside Height:

0.872 inches

Waveguide Outside Height:

1.000 inches

Flange Connecting Facility And Quantity:

6 threaded hole all flanges all connection facilities

Flange Style:

Choke type all flanges

Waveguide Length:

4.375 inches

NSN 5985-01-040-3122 Waveguide Assembly - Page 2 of 2

A073a0



Waveguide Center To Center Distance:
6.875 inches
Special Features:
5.500 in. Diameter w/ six 0.313 in. Diameter holes on 4.563 bsc mtg plate, mounted midway on the waveguide
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy 5052 all tubing segment and flange
Surface Treatment:
Paint all tubing segment and flange outside surfaces
Style Designator:
Offset bend type
Thread Series Designator:
Unf all flanges all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: