# NSN 5985-01-040-4157

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-040-4157

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### **Thread Class:**

2b second flange all connection facilities

## **Thread Direction:**

Right-hand second flange all connection facilities

## Tubing Wall Construction Style:

Corrugated single tubing segment

# Flange Quantity:

```
2
```

#### Flange Inside Width:

1.253 inches first flange and 1.256 inches first flange

#### Flange Inside Height:

0.628 inches first flange and 0.631 inches first flange

#### Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

## Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

#### Flange Inside Diameter:

1.610 inches second flange and 1.640 inches second flange

# Flange Depth:

0.610 inches second flange and 0.640 inches second flange

## Flange Connecting Hole Diameter:

0.169 inches first flange all connection facilities and 0.172 inches first flange all connection facilities

# Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.06

Maximum Operating Pressure:

25.0 pounds per square inch gage

#### Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

#### **Thread Size:**

0.164 inches second flange all connection facilities

#### Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

## Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

## Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

# Flange Connecting Facility And Quantity:

4 unthreaded hole first flange all connection facilities

# NSN 5985-01-040-4157

Waveguide Assembly - Page 2 of 2

ase К

Flange Style: Cover type first flange Waveguide Center To Center Distance: 11.230 inches Waveguide Height: 4.560 inches Flexibility: Flexible single tubing segment Material: Plastic single tubing jacket **Precious Material And Location:** Internal tubing segment surfaces silver **Precious Material:** Silver Surface Treatment: Silver single tubing segment inside surfaces **Style Designator:** Double bend type **Thread Series Designator:** Unc second flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A073a0

---