NSN 5985-01-040-4184

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-040-4184

View Online at https://aerobasegroup.com/nsn/5985-01-040-4184
Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Err-090
Overall Length:
1.240 inches
Overall Diameter:
0.390 inches
Operating Tempurature Range:
+0.0/+50.0 degrees celsius
Voltage Standing Wave Ratio:
1.15 and 1.30
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz and +4.0/+12.4 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 12.400 gigahertz
Test Data Document:
81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5985-01-040-4184

Fixed Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A20000