NSN 5985-01-041-1441

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-041-1441

Application Design: Transmission line **Body Style:** Coaxial type **Overall Length:** Between 2.690 inches and 2.810 inches **Overall Height:** Between 2.560 inches and 2.680 inches **Overall Width:** Between 5.940 inches and 6.000 inches **Voltage Standing Wave Ratio:** 1.20 and 1.30 and 1.50 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 0.5 watts average and 350.0 watts peak **Insertion Loss At Minimum Attenuation In Maximum Decibels:** 0.25 **Overall Attenuation Range In Decibels:** +0.0/+12.0 **Attenuation Variation Method:** Stepped **Step Position Quantity:** 12 **Attenuation Per Step In Decibels:** 1.0 **Mounting Facility Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 1.000 gigahertz **Adjustment Device Type And Quantity:** Impedance Rating In Ohms: 50.0 input-output **Test Data Document:** 81349-mil-a-24215 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 connector, coaxial, female

Specification Data:

81349-mil-a-24215/6 government specification

Shelf Life:

N/a

NSN 5985-01-041-1441

Variable Attenuator - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A223a0