NSN 5985-01-041-4905

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-041-4905

| Application Design: |
|------------------------------------------------------------|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 3.810 inches |
| Overall Height: |
| 2.200 inches |
| Overall Width: |
| 1.880 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 0.750 inches |
| Operating Tempurature Range: |
| -20.0/+125.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.15 and 1.00 |
| Coaxial Connector Series Designation: |
| Sma |
| Power Rating: |
| 0.5 watts average |
| Insertion Loss At Minimum Attenuation In Maximum Decibels: |
| 0.1 |
| Overall Attenuation Range In Decibels: |
| +0.0/+100.0 |
| Attenuation Variation Method: |
| Stepped |
| Step Position Quantity: |
| 10 |
| Attenuation Per Step In Decibels: |
| 10.0 |
| Frequency Range: |
| Between 25.000 megahertz and 35.000 megahertz |
| Overall Attenuation Accuracy In Decibels: |
| -0.20/+0.20 |
| Adjustment Device Type And Quantity: |
| 1 shaft |
| Shaft Type: |
| Round |
| Terminal Type And Quantity: |

2 connector, coaxial, female

NSN 5985-01-041-4905

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0