

View Online at <https://aerobasegroup.com/nsn/5985-01-047-2373>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

7.285 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.453 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

Overall Height:

1.200 inches

Overall Width:

1.750 inches

Operating Temperature Range:

-20.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 and 1.50

Coaxial Connector Series Designation:

Bnc

Power Rating:

500.0 milliwatts average and 1.0 kilowatts peak

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

2.0

Overall Attenuation Range In Decibels:

+0.0/+102.0

Attenuation Accuracy Reference Frequency:

500.0 megahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

9

Attenuation Per Step In Decibels:

1.0 and 2.0 and 3.0 and 6.0 and 10.0 and 20.0 and 20.0 and 20.0 and 20.0

Mounting Facility Type And Quantity:

2 threaded hole

Frequency Range:

Between 0.000 gigahertz and 1.000 gigahertz

Overall Attenuation Accuracy In Decibels:

-1.00/+1.00

Segment Attenuation Range In Decibels:

+0.00/+102.00

Segment Attenuation Accuracy In Decibels:

-1.00/+1.00

Mounting Thread Quantity:

32 per inch

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0