NSN 5985-01-047-6463

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

Body Surface Treatment:

Metal

Err-090

Body Style:

Any acceptable

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-01-047-6463

| 3.490 inches | | | | | | | |
|---|--|--|--|--|--|--|--|
| Overall Diameter: | | | | | | | |
| 1.650 inches | | | | | | | |
| End Application: | | | | | | | |
| F/tf-15a aircraft age. | | | | | | | |
| Voltage Standing Wave Ratio: | | | | | | | |
| 1.30 | | | | | | | |
| Input Impedance Rating In Ohms: | | | | | | | |
| 50.0 | | | | | | | |
| Output Impedance Rating In Ohms: | | | | | | | |
| 50.0 | | | | | | | |
| Coaxial Connector Series Designation: | | | | | | | |
| N | | | | | | | |
| Rf Signal Attenuation In Decibels: | | | | | | | |
| 20.0 | | | | | | | |
| Voltage Standing Wave Ratio Frequency Range: | | | | | | | |
| +0.0/+8.0 gigahertz | | | | | | | |
| Attenuation Accuracy Reference Frequency: | | | | | | | |
| 8.0 gigahertz | | | | | | | |
| Attenuation Accuracy In Decibels: | | | | | | | |
| -0.60/+0.60 | | | | | | | |
| Connection Type Per Function: | | | | | | | |
| Female input and male output | | | | | | | |
| Mounting Method: | | | | | | | |
| Connector | | | | | | | |
| Terminal Type And Quantity: | | | | | | | |
| 2 connector | | | | | | | |
| Frequency Range: | | | | | | | |
| | | | | | | | |
| Between 0.000 hertz and 8.000 gigahertz | | | | | | | |
| Between 0.000 hertz and 8.000 gigahertz Fsc Application Data: | | | | | | | |
| | | | | | | | |
| Fsc Application Data: | | | | | | | |
| Fsc Application Data: Antennas, waveguides, and related equipment | | | | | | | |

NSN 5985-01-047-6463

Fixed Attenuator - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A20000