## NSN 5985-01-047-6463

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:

**Body Surface Treatment:** 

Metal

Err-090

**Body Style:** 

Any acceptable

Overall Length:



View Online at https://aerobasegroup.com/nsn/5985-01-047-6463

3.490 inches							
Overall Diameter:							
1.650 inches							
End Application:							
F/tf-15a aircraft age.							
Voltage Standing Wave Ratio:							
1.30							
Input Impedance Rating In Ohms:							
50.0							
Output Impedance Rating In Ohms:							
50.0							
Coaxial Connector Series Designation:							
N							
Rf Signal Attenuation In Decibels:							
20.0							
Voltage Standing Wave Ratio Frequency Range:							
+0.0/+8.0 gigahertz							
Attenuation Accuracy Reference Frequency:							
8.0 gigahertz							
Attenuation Accuracy In Decibels:							
-0.60/+0.60							
Connection Type Per Function:							
Female input and male output							
Mounting Method:							
Connector							
Terminal Type And Quantity:							
2 connector							
Frequency Range:							
Between 0.000 hertz and 8.000 gigahertz							
Between 0.000 hertz and 8.000 gigahertz  Fsc Application Data:							
Fsc Application Data:							
Fsc Application Data: Antennas, waveguides, and related equipment							

## NSN 5985-01-047-6463

Fixed Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A20000