NSN 5985-01-048-0174 Fixed Attenuator - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5985-01-048-0174 |
|---|
| Application Design: |
| Transmission line |
| Body Material: |
| Any acceptable |
| Body Style: |
| Err-090 |
| Overall Length: |
| 2.750 inches |
| Overall Diameter: |
| 0.840 inches |
| Operating Tempurature Range: |
| -40.0/+55.0 degrees celsius |
| Voltage Standing Wave Ratio: |
| 1.25 |
| Input Impedance Rating In Ohms: |
| 50.0 |
| Output Impedance Rating In Ohms: |
| 50.0 |
| Coaxial Connector Series Designation: |
| N . |
| Power Rating: |
| 2.0 watts average and 1.0 kilowatts peak |
| Rf Signal Attenuation In Decibels: |
| 20.0 |
| Voltage Standing Wave Ratio Frequency Range: |
| +0.0/+12.4 gigahertz |
| Attenuation Accuracy In Decibels: |
| -0.40/+0.40 |
| Connection Type Per Function: |
| Female output and male input |
| Mounting Method: |
| Connector |
| Terminal Type And Quantity: |
| 2 connector |
| Frequency Range: |
| Between 0.000 hertz and 12.400 gigahertz |
| Test Data Document: |
| 81349-mil-a-3933 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5985-01-048-0174

Fixed Attenuator - Page 2 of 2



Demilitarization:

No

Fiig:

A20000