## NSN 5985-01-049-0151

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-049-0151
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.770 inches
Overall Diameter:
0.800 inches
Operating Tempurature Range:
-54.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.07
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
2.0 watts average and 200.0 watts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:

Connector

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 18.000 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

## NSN 5985-01-049-0151

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000