

View Online at <https://aerobasegroup.com/nsn/5985-01-050-4888>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 single bend h-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.255 inches second flange

Flange Inside Height:

0.630 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Waveguide Longer Offset Distance:

2.380 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Offset Distance:

2.380 inches

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

Surface Treatment:

Paint single tubing segment and flange outside surfaces

Style Designator:

Bend type

Thread Series Designator:

Unc first flange single connection facility

Fsc Application Data:

Radar equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0