## NSN 5985-01-050-5772

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-050-5772

Application Design:
Transmission line
Body Material:
Any acceptable
Body Style:
Err-090
Body Surface Treatment:
Anodized and silver plated, qq-s-365
Overall Length:
3.230 inches
Overall Diameter:
1.000 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Ν
Power Rating:
10.0 watts average and 5.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Temperature Sensitivity Attenuation In Decibels:
0.0050
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.000 gigahertz
Detriotin 0.000 horiz and 4.000 giganeriz

## NSN 5985-01-050-5772

Fixed Attenuator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

