NSN 5985-01-052-0784

Fixed Attenuator - Page 1 of 2

Application Design:
Transmission line
Body Material:



View Online at https://aerobasegroup.com/nsn/5985-01-052-0784

Steel, stainless					
Body Style:					
1b round, terminal/terminals in opposite surface					
Body Surface Treatment:					
Any acceptable					
Overall Length:					
0.860 inches					
Overall Diameter:					
0.280 inches					
Operating Tempurature Range:					
-65.0/+125.0 degrees celsius					
Voltage Standing Wave Ratio:					
1.07					
Input Impedance Rating In Ohms:					
50.0					
Output Impedance Rating In Ohms:					
50.0					
Coaxial Connector Series Designation:					
Sma					
Power Rating:					
2.0 watts average					
Rf Signal Attenuation In Decibels:					
2.0					
Voltage Standing Wave Ratio Frequency Range:					
+0.0/+18.0 gigahertz					
Attenuation Accuracy Reference Frequency:					
18.0 gigahertz					
Attenuation Accuracy In Decibels:					
-0.30/+0.30					
Mounting Method:					
Connector					
Terminal Type And Quantity:					
2 connector					
Frequency Range:					
Between 0.000 hertz and 18.000 gigahertz					
Specification Data:					
49671-2387927 manufacturers specification control					
Fsc Application Data:					
Antennas, waveguides, and related equipment					

NSN 5985-01-052-0784

Fixed Attenuator - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000