

View Online at <https://aerobasegroup.com/nsn/5985-01-052-0785>

**Application Design:**

Transmission line

**Body Material:**

Steel, stainless

**Body Style:**

1b round, terminal/terminals in opposite surface

**Overall Length:**

0.860 inches

**Overall Diameter:**

0.280 inches

**Operating Temperature Range:**

-65.0/+125.0 degrees celsius

**End Application:**

Wasp class lhd; nimitz class cvn; an/wlr-1h surface countermeasure receiver set; u-2 support equipment; sturgeon class ssn (637);

an/apr-4 (v) radar warning system; an/wsc-6 shf satcom radio; an/msr-t4; forrestal class cv

**Voltage Standing Wave Ratio:**

1.07

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Sma

**Power Rating:**

2.0 watts average

**Rf Signal Attenuation In Decibels:**

3.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+18.0 gigahertz

**Attenuation Accuracy Reference Frequency:**

18.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 18.000 gigahertz

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Surfaces gold

**Precious Material:**

Gold

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000