NSN 5985-01-053-4164

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-053-4164 **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Passivated **Overall Length:** 2.680 inches **Overall Diameter:** 0.827 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Voltage Standing Wave Ratio:** 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Ν **Power Rating:** 5.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 50.0 **Voltage Standing Wave Ratio Frequency Range:** +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz **Attenuation Accuracy Reference Frequency:** 12.4 gigahertz **Attenuation Accuracy In Decibels:** -0.75/+0.75 **Unpackaged Unit Weight:** 2.600 ounces **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Precious Material And Location: Female contact surfaces gold

NSN 5985-01-053-4164

Fixed Attenuator - Page 2 of 2



Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000