

View Online at <https://aerobasegroup.com/nsn/5985-01-054-5561>

Application Design:

Transmission line

Body Material:

Aluminum

Body Style:

1b round, terminal/terminals in opposite surface

Body Surface Treatment:

Anodized

Overall Length:

2.750 inches

Overall Diameter:

1.610 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

End Application:

Airport surveillance radar (asr)

Voltage Standing Wave Ratio:

1.15 and 1.20 and 1.25

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

N

Power Rating:

10.0 watts average and 2.0 kilowatts peak

Rf Signal Attenuation In Decibels:

10.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz

Attenuation Accuracy In Decibels:

-0.50/+0.50

Connection Type Per Function:

Female output and male input

Mounting Method:

Terminal

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 12.400 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000