

View Online at <https://aerobasegroup.com/nsn/5985-01-054-6044>

Application Design:

Transmission line

Body Material:

Steel, qq-s-763, class 303, cond a or brass, qq-b-626, comp 22, 1/2h

Body Style:

Err-090

Body Surface Treatment:

Gold plated

Overall Length:

1.375 inches

Overall Diameter:

0.360 inches

Operating Temperature Range:

-54.0/+100.0 degrees celsius

End Application:

An/alr-62 (v) peculiar

Voltage Standing Wave Ratio:

1.20

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Bnc

Power Rating:

10.0 milliwatts peak

Rf Signal Attenuation In Decibels:

4.0

Attenuation Accuracy Reference Frequency:

30.0 megahertz

Attenuation Accuracy In Decibels:

-0.30/+0.30

Connection Type Per Function:

Female input and male output

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 7.000 gigahertz

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000