# NSN 5985-01-054-6044

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-054-6044

## Application Design:

Transmission line

#### **Body Material:**

Steel, qq-s-763, class 303, cond a or brass, qq-b-626, comp 22, 1/2h

### **Body Style:**

Err-090

#### **Body Surface Treatment:**

Gold plated

### **Overall Length:**

1.375 inches

#### **Overall Diameter:**

0.360 inches

#### **Operating Tempurature Range:**

-54.0/+100.0 degrees celsius

#### End Application:

## An/alr-62 (v) peculair

### Voltage Standing Wave Ratio:

1.20

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Bnc

#### **Power Rating:**

10.0 milliwatts peak

#### **Rf Signal Attenuation In Decibels:**

4.0

#### Attenuation Accuracy Reference Frequency:

30.0 megahertz

#### Attenuation Accuracy In Decibels:

-0.30/+0.30

## Connection Type Per Function:

Female input and male output

## Mounting Method:

Connector

## Terminal Type And Quantity:

2 connector

## Frequency Range:

Between 0.000 hertz and 7.000 gigahertz

Shelf Life:

N/a

# NSN 5985-01-054-6044

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000

