NSN 5985-01-054-6697

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-054-6697

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.120 inches
Overall Height:
2.590 inches
Overall Width:
1.870 inches
Scale Linearity:
Linear
Scale Division Quantity:
10
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Voltage Standing Wave Ratio:
1.20
Coaxial Connector Series Designation:
Tnc
Power Rating:
1.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Vernier Scale Division Quantity:

10

NSN 5985-01-054-6697

Variable Attenuator - Page 2 of 2



Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 gigahertz and 2.000 gigahertz **Overall Attenuation Accuracy In Decibels:** -0.10/+0.50 **Mounting Thread Quantity:** 32 per inch **Adjustment Device Type And Quantity:** 1 shaft **Shaft Type:** Round **Mounting Facility Screw Thread Diameter:** 0.164 inches Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, male Shelf Life: N/a **Unit Of Measure:** Demilitarization:

Yes - demil/mli

Fiig: A223a0