## NSN 5985-01-054-9841

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-054-9841 **Application Design:** Transmission line **Body Material:** Steel, qq-s-763, class 303, cond a or brass, qq-b-626, comp 22, 1/2h **Body Style:** Err-090 **Body Surface Treatment:** Gold plated **Overall Length:** 1.375 inches **Overall Diameter:** 0.360 inches **Operating Tempurature Range:** -54.0/+100.0 degrees celsius **End Application:** 5865-01-048-9989 **Voltage Standing Wave Ratio:** 1.20 **Input Impedance Rating In Ohms:** 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Tsm connectors Rf Signal Attenuation In Decibels: 5.0 **Attenuation Accuracy Reference Frequency:** 30.0 megahertz **Attenuation Accuracy In Decibels:** -0.30/+0.30 **Connection Type Per Function:** Female input and male output **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 7.000 gigahertz Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5985-01-054-9841

Fixed Attenuator - Page 2 of 2



Fiig:

A20000