

View Online at <https://aerobasegroup.com/nsn/5985-01-055-5655>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange first connection facility

Thread Direction:

Right-hand first flange first connection facility

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.628 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.860 inches second flange and 1.890 inches second flange

Flange Outside Height:

1.860 inches second flange and 1.890 inches second flange

Flange Depth:

0.610 inches first flange and 0.640 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange second connection facility and 0.172 inches second flange second connection facility

Voltage Standing Wave Ratio:

1.08

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Thread Size:

0.164 inches first flange first connection facility

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

Between 2.985 inches and 3.015 inches

Special Features:

Has a spacer brazed to one flange

Flexibility:

Flexible single tubing segment

Material:

Copper alloy single tubing segment

Surface Treatment:

Silver single tubing segment all surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange first connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0