# NSN 5985-01-055-8556

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-055-8556

# Application Design:

Transmission line

#### **Body Material:**

Steel, qq-s-763, class 303, cond a or brass, qq-b-626, comp 22, 1/2h

#### **Body Style:**

Err-090

### **Body Surface Treatment:**

Gold plated

#### **Overall Length:**

1.375 inches

#### **Overall Diameter:**

0.360 inches

#### **Operating Tempurature Range:**

-54.0/+100.0 degrees celsius

#### **End Application:**

#### 5865-01-048-9989

### Voltage Standing Wave Ratio:

1.20

#### Input Impedance Rating In Ohms:

50.0

#### **Output Impedance Rating In Ohms:**

50.0

#### **Coaxial Connector Series Designation:**

Tsm connectors

#### **Rf Signal Attenuation In Decibels:**

4.50

#### **Attenuation Accuracy Reference Frequency:**

30.0 megahertz

# Attenuation Accuracy In Decibels:

-0.30/+0.30

#### **Connection Type Per Function:**

Female input and male output

#### **Terminal Type And Quantity:**

2 connector

#### **Frequency Range:**

Between 0.000 hertz and 7.000 gigahertz

#### Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

# NSN 5985-01-055-8556

Fixed Attenuator - Page 2 of 2

**Fiig:** A20000

