NSN 5985-01-056-1090

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-056-1090

Application Design:
Transmission line
Body Style:
Rectangular, terminals on one surface
Overall Length:
3.000 inches
Overall Height:
1.000 inches
Overall Width:
0.500 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.500 inches
Shaft Length:
0.500 inches
Distance Between Mounting Facility Centers:
1.375 inches
Voltage Standing Wave Ratio:
1.50
Power Rating:
200.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+25.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
2 flange w/mounting hole
Frequency Range:
Between 7.900 gigahertz and 8.400 gigahertz
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round, flatted
Terminal Type And Quantity:
2 connector, coaxial, female

N/a

NSN 5985-01-056-1090

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0