## NSN 5985-01-057-5088

Fixed Attenuator - Page 1 of 2



-
View Online at https://aerobasegroup.com/nsn/5985-01-057-5088
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.210 inches
Overall Diameter:
0.375 inches
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-0.30/+0.30
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector

**Terminal Type And Quantity:** 

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

**Fsc Application Data:** 

Antennas, waveguides, and related equipment

## NSN 5985-01-057-5088

Fixed Attenuator - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000