NSN 5985-01-057-6856

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-057-6856

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

1.256 inches second flange

Flange Inside Height:

0.631 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.625 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.03

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Maximum Operating Pressure:

25.0 pounds per square inch gage

Waveguide Outside Width:

1.250 inches

Waveguide Inside Width:

1.122 inches

Waveguide Inside Height:

0.497 inches

Waveguide Outside Height:

0.625 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

48.000 inches

NSN 5985-01-057-6856

Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid all tubing segment
Material:
Aluminum first flange
Style Designator:
Straight type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A073a0