

View Online at <https://aerobasegroup.com/nsn/5985-01-057-8914>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Tubing Wall Construction Style:

Interlocked single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.250 inches second flange and 1.256 inches second flange

Flange Inside Height:

0.625 inches second flange and 0.631 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Inside Diameter:

1.492 inches first flange and 1.498 inches first flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.166 inches second flange single connection facility and 0.172 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.06

Maximum Operating Pressure:

5.0 pounds per square inch gage

Thread Size:

0.164 inches first flange single connection facility

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Waveguide Length:

Between 4.984 inches and 5.016 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber synthetic single tubing jacket

Precious Material And Location:

Tubing internal surfaces silver and flange inside surfaces silver

Surface Treatment:

Paint all flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0