NSN 5985-01-058-4307

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-058-4307
Application Design:
Transmission line
Body Material:
Metal
Body Style:
Err-090
Body Surface Treatment:
Anodized
Overall Length:
4.280 inches
Overall Diameter:
1.000 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
25.0 watts average and 3.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-1.00/+1.00
Connection Type Per Function:
Female input and female output
Mounting Method:
Connector
Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Precious Material And Location:

Connector surfaces silver

NSN 5985-01-058-4307 Fixed Attenuator - Page 2 of 2



Precious Material:	
Silver	
Fsc Application Data:	
Antennas, waveguides, and related equipment	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A20000