NSN 5985-01-058-6655

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-058-6655

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.310 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.880 inches
Overall Height:
2.080 inches
Overall Width:
2.600 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.560 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+6.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 megahertz and 20.000 megahertz
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
2 shaft
Mounting Facility Pattern:

Four position rectangular

NSN 5985-01-058-6655

Variable Attenuator - Page 2 of 2



Shaft Type:	Sh	aft	Τv	pe:
-------------	----	-----	----	-----

Round, slotted

Mounting Facility Screw Thread Diameter:

0.112 inches

Impedance Rating In Ohms:

75.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0