NSN 5985-01-058-7826

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-058-7826
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Err-090
Body Surface Treatment:
Any acceptable
Overall Length:
1.240 inches
Overall Diameter:
Between 0.350 inches and 0.385 inches
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
2.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
3.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female input and male output
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 0.000 hertz and 4.500 gigahertz
Test Data Document:
81349-mil-a-3933/15 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

NSN 5985-01-058-7826

Fixed Attenuator - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A20000