## NSN 5985-01-058-7826

Fixed Attenuator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5985-01-058-7826

## **Application Design:** Transmission line **Body Material:** Steel, stainless **Body Style:** Err-090 **Body Surface Treatment:** Any acceptable **Overall Length:** 1.240 inches **Overall Diameter:** Between 0.350 inches and 0.385 inches **Operating Tempurature Range:** -55.0/+85.0 degrees celsius Voltage Standing Wave Ratio: 1.25 Input Impedance Rating In Ohms: 50.0 **Output Impedance Rating In Ohms:** 50.0 **Coaxial Connector Series Designation:** Sma **Power Rating:** 2.0 watts average and 1.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.5 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Connection Type Per Function:** Female input and male output **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector **Frequency Range:** Between 0.000 hertz and 4.500 gigahertz **Test Data Document:** 81349-mil-a-3933/15 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

## NSN 5985-01-058-7826

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A20000

