NSN 5985-01-059-2560



Variable Attenuator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5985-01-059-2560 **Application Design:** Printed circuit board **Body Style:** Irregular **Overall Length:** Between 0.672 inches and 0.704 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.350 inches **Overall Height:** Between 0.547 inches and 0.579 inches **Overall Width:**

Between 0.640 inches and 0.672 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.250 inches

Operating Tempurature Range:

-65.0/+85.0 degrees celsius

Voltage Standing Wave Ratio:

1.02

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 terminal

Frequency Range:

Between 15.000 megahertz and 100.000 megahertz

Adjustment Device Type And Quantity:

1 electronic, current controlled

Mounting Facility Pattern:

Four position rectangular

Criticality Code Justification:

Feat

Impedance Rating In Ohms:

50.0 input-output

Special Features:

Weapon system essential

Terminal Type And Quantity:

4 pin

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

NSN 5985-01-059-2560

Variable Attenuator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A223a0