NSN 5985-01-063-4565

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-063-4565
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.505 inches
Overall Height:
1.825 inches
Overall Width:
1.312 inches
Distance Between Mounting Facility Centers:
0.875 inches
Operating Tempurature Range:
+20.0/+85.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 100.0 watts peak
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+79.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
79
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded stud
Frequency Range:
Between 0.000 gigahertz and 1.000 gigahertz
Mounting Thread Quantity:
32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Two position in-line

Mounting Facility Screw Thread Diameter:

0.138 inches

NSN 5985-01-063-4565

Variable Attenuator - Page 2 of 2



Impedance	Rating	In	Ohms:
-----------	--------	----	-------

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0