## NSN 5985-01-064-2522

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-064-2522

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.625 inches
Overall Height:
1.875 inches
Overall Width:
2.578 inches
Scale Linearity:
Linear
Scale Division Quantity:
79
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.40
Coaxial Connector Series Designation:
Bnc
Power Rating:
500.0 milliwatts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+79.0
Attenuation Accuracy Reference Frequency:
30.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
79
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
1 bushing
Frequency Range:
Between 0.000 gigahertz and 4.500 gigahertz
Overall Attenuation Accuracy In Decibels:
-2.00/+2.00
Adjustment Device Type And Quantity:

1 knob

## NSN 5985-01-064-2522

Variable Attenuator - Page 2 of 2



Impedance Ra	ating In	Ohms:
--------------	----------	-------

50.0 input-output

**Terminal Type And Quantity:** 

2 connector, coaxial, female

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A223a0