NSN 5985-01-065-3077

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-065-3077

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.562 inches
Overall Height:
2.188 inches
Overall Width:
1.875 inches
Unthreaded Mounting Hole Diameter:
0.219 inches
Distance Between Mounting Facility Centers:
1.062 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average
Overall Attenuation Range In Decibels:
+0.0/+10.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 unthreaded hole
Frequency Range:
Between 0.000 gigahertz and 2.000 gigahertz
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female

NSN 5985-01-065-3077

Variable Attenuator - Page 2 of 2



Fsc Application Data	Fsc	Ap	plic	atio	n D	ata
----------------------	-----	----	------	------	-----	-----

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0