NSN 5985-01-068-5198

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-068-5198

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.430 inches
Overall Height:
1.390 inches
Overall Width:
2.030 inches
Scale Linearity:
Nonlinear
Scale Division Quantity:
127
Distance Between Mounting Facility Centers:
115.870 inches
Operating Tempurature Range:
-0.0/+55.0 degrees celsius
Coaxial Connector Series Designation:
Sma
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
1.2
Overall Attenuation Range In Decibels:
+0.0/+127.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 1000.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.20/+0.20
Segment Attenuation Range In Decibels:
+0.00/+63.00
Mounting Thread Quantity:

32 per inch

NSN 5985-01-068-5198

Variable Attenuator - Page 2 of 2



Adjustment Device Type And Quantity: 16 slotted screw Mounting Facility Pattern: Two position in-line Mounting Facility Screw Thread Diameter: 0.164 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A223a0