NSN 5985-01-068-9550

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-068-9550

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
Any acceptable
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.230 inches
Overall Height:
1.500 inches
Overall Width:
Any acceptable
Scale Linearity:
Linear
Unthreaded Mounting Hole Diameter:
0.164 inches
Operating Tempurature Range:
-10.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N or bnc
Overall Attenuation Range In Decibels:
+0.0/+40.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.700 gigahertz and 2.900 gigahertz
Adjustment Device Type And Quantity:
1 lever
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
75.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, male
Shelf Life:

N/a

NSN 5985-01-068-9550

Variable Attenuator - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0