NSN 5985-01-069-4212

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-069-4212

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.220 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.220 inches
Overall Height:
2.712 inches
Overall Width:
1.625 inches
Operating Tempurature Range:
-0.0/+71.0 degrees celsius
Voltage Standing Wave Ratio:
1.20
Mounting Facility Screw Thread Series Designator:
Unc
Waveguide Flange Type:
Choke
Waveguide Flange Designation:
Ug-136b/u
Overall Attenuation Range In Decibels:
+0.2/+10.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 8.200 gigahertz and 12.400 gigahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Marie Carlo Facilità Como Timo I Diagnos
Mounting Facility Screw Thread Diameter:
0.164 inches

2 flange

NSN 5985-01-069-4212

Variable Attenuator - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0