NSN 5985-01-071-0510

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-01-071-0510

Transmission line Body Material: Aluminum Body Style: Err-090 Body Surface Treatment: Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function: Female output and male input
Aluminum Body Style: Err-090 Body Surface Treatment: Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Body Style: Err-090 Body Surface Treatment: Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Err-090 Body Surface Treatment: Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Body Surface Treatment: Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Anodized Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Overall Length: 2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
2.720 inches Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Overall Diameter: 1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
1.620 inches Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Operating Tempurature Range: +0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
+0.0/+125.0 degrees celsius Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Voltage Standing Wave Ratio: 1.15 and 1.20 and 1.25 Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Input Impedance Rating In Ohms: 50.0 Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Output Impedance Rating In Ohms: 50.0 Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Coaxial Connector Series Designation: N Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Power Rating: 10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
10.0 watts average and 2.0 kilowatts peak Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Rf Signal Attenuation In Decibels: 30.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Voltage Standing Wave Ratio Frequency Range: +0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
+0.0/+4.0 gigahertz and +4.0/+8.0 gigahertz and +8.0/+12.4 gigahertz Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Attenuation Accuracy In Decibels: -0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
-0.75/+0.75 Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
Temperature Sensitivity Attenuation In Decibels: 0.0001 Connection Type Per Function:
0.0001 Connection Type Per Function:
Connection Type Per Function:

Female output and male input
Temale output and male input
Mounting Method:
Terminal
Terminal Type And Quantity:
2 connector
•
2 connector

N/a

NSN 5985-01-071-0510

Fixed Attenuator - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A20000